

INDEX SELECTION ENGINE FOR SPATIAL DATABASE SYSTEM

MARUTO MASSERIE SARDADI

UNIVERSITI TEKNOLOGI MALAYSIA

INDEX SELECTION ENGINE FOR SPATIAL DATABASE SYSTEM

MARUTO MASSERIE SARDADI

A Thesis submitted in fulfilment of the
requirement for the award for the degree of
Master of Science (Computer Science)

Faculty of Computer Science & Information Systems
Universiti Teknologi Malaysia

AUGUST 2010

To my God, Allah 'azza wa jalla

and

Dedicated to my mother and father whose love, encouragement and values will
always guide and inspire me.

Idawati

Baskoro Sardadi

and

To my brother, Baruno Sardadi and my wife, Maulidya Maherany

In the hope that they will be encouraged to strive for the best and thank you so much
for being so patient and being there for me.

ACKNOWLEDGMENT

In preparing this thesis, I was in contact with many people, researchers, academicians, and practitioners. They have contributed towards my understanding and thoughts. In particular, I wish to express my sincere appreciation to my main thesis supervisor, Assoc. Prof. Daut Daman, for encouragement, guidance, critics and friendship. I am also very thankful to my co-supervisors Dr. Mohd Shafry Mohd Rahim and En. Zahabidin Jupri for their guidance, advices and motivation. And another lecture was also gave some supports in my study, En. Daud Kasmuni. Without their continued support and interest, this thesis would not have been the same as presented here.

I am also indebted to Universiti Teknologi Malaysia (UTM) for funding my Master study. Librarians at UTM also deserve special thanks for their assistance in supplying the relevant literatures.

My fellow from Indonesian Student Association (PPI) should also be recognized for their support. My sincere appreciation also extends to all my colleagues and others who have provided assistance at various occasions. Their views and tips are useful indeed. Unfortunately, it is not possible to list all of them in this limited space. I am grateful to all my family members.

ABSTRACT

The latest mobile Geographical Information System (GIS) technology is useful to manage spatial components of various daily business projects in corporate databases. It is important to apply proper geographical analysis efficiently in a wireless application. However, one of the problems of wireless internet is system bottlenecks that can slow down data processing in Mobile GIS. Spatial data indexing is one of the methods to speed up spatial queries. The existing spatial data indexing can only change the index used. However, an indexing method is only better for some ranges of data and conditions. The objective of this research is to speed up access to spatial database system by using spatial index selection engine. This research introduces an index selection engine for spatial database system for every condition and range of data, on top of the basic index structure. The index selection engine, which is called QuadRtree Selection engine, uses a rule-based Knowledge Base Expert System (KBES) to select between R-tree and Quadtree spatial data indices. These spatial data indexing methods are the best spatial data indexing methods among many other existing spatial index methods for low-dimensional spatial data which have different advantages and disadvantages based on the condition of spatial data. The result of using the proposed method can save time up to 42.5% compared to not using this method.

ABSTRAK

Teknologi Sistem Maklumat Geografi (GIS) mudah alih terkini berguna untuk mengurus komponen ruang dalam pelbagai urusan harian projek perniagaan pada pangkalan data koprat. Teknologi ini penting untuk penggunaan analisa geografi secara efisien dalam aplikasi tanpa wayar. Namun, teknologi tanpa wayar ini boleh melambatkan proses pemindahan data akibat daripada kesesakan laluan sistem di dalam teknologi GIS mudah alih. Mengindeks data ruang merupakan salah satu kaedah untuk mempercepatkan pertanyaan berasaskan ruang. Kaedah peningkatan mengindeks data ruang yang sedia ada hanya boleh mengubah indeks yang digunakan. Namun, kaedah mengindeks hanya lebih baik untuk beberapa julat data dan keadaan. Objektif penyelidikan ini adalah untuk mempercepatkan capaian pada sistem pangkalan data ruang dengan menggunakan mesin pemilihan indeks ruang. Penyelidikan ini memperkenalkan mesin pemilihan indeks untuk sistem pangkalan data ruang dalam setiap keadaan dan pelbagai julat data, ke atas struktur asas indeks. Mesin pemilihan indeks ini, yang disebut mesin pemilihan QuadRtree, menggunakan Pangkalan Pengetahuan Sistem Pakar berasaskan peraturan untuk memilih antara indeks data ruang R-tree dan Quadtree. Kaedah mengindeks data ruang ini adalah kaedah mengindeks data ruang yang terbaik di antara banyak kaedah pengindeks data ruang yang sedia ada untuk data yang berdimensi rendah di mana mempunyai perbezaan kelebihan dan kekurangan berdasarkan keadaan data ruang. Keputusan menggunakan kaedah yang dicadangkan boleh menjimatkan masa sehingga 42.5% dibandingkan dengan tidak menggunakan kaedah ini.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xii
	LIST OF ABBREVIATIONS	xv
	LIST OF APPENDICES	xvii
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Problem Background	3
	1.3 Problem Statement	14
	1.4 Goal and Objectives	15
	1.5 Scope of the Study	15
	1.6 Expected Contribution and Summary	16

2	LITERATURE REVIEW	18
2.1	Introduction	18
2.2	Mobile GIS	19
2.2.1	Mobile GIS Architecture	21
2.2.2	Wireless Communication in Mobile GIS	22
2.2.3	Issues in Mobile GIS	24
2.3	Spatial Data	32
2.3.1	Spatial Database	32
2.3.2	Spatial Indexing	33
2.3.2.1	Kd-tree	34
2.3.2.2	Z-order	35
2.3.2.3	UB-tree	35
2.3.2.4	Octree	36
2.3.2.5	Grid	36
2.3.2.6	R-trees	37
2.3.2.7	Quadtree	40
2.3.2.8	Discussion on Indexing Issues in Spatial Data	44
2.4	Hybrid Quadtree and R-tree	44
2.5	R-tree and Quadtree Indexing Issues	45
2.6	Selection Method for Tuning Spatial Database in Mobile GIS	51
2.6.1	Tuning the Spatial Database	51
2.6.2	Issues and Problems in the Selection Method	52
2.6.3	Rule Base - Expert Knowledge for QuadR- tree Selection Engine	62
2.7	Discussion	67
2.8	Summary	68
3	RESEARCH METHODOLOGY	69
3.1	Introduction	69
3.2	Research Framework	70

3.3	R-tree and Quadtree Spatial Data Indexing	72
3.4	Selection Method	74
3.5	Implementation of Mobile GIS	83
3.6	Testing and Evaluation	84
3.7	Discussion & Summary	87
4	IMPLEMENTATION & TESTING	89
4.1	Introduction	89
4.2	Spatial Database Development	90
4.2.1	R-tree Spatial Data Indexing	96
4.2.2	Quadtree Spatial Data Indexing	101
4.3	Analyzing and Exploring the Knowledge Based for Rule-Based Data Set	104
4.4	Rule-Based Knowledge Experts	110
4.5	QuadRtree Indexing Selection Engine	115
4.6	Implementation of QuadRtree in Mobile GIS Application	119
4.7	Summary	124
5	RESULT & EVALUATION	125
5.1	Introduction	125
5.2	Mobile GIS Application	126
5.3	Evaluating the Geographical Data	149
5.3.1	Evaluating the Geographical Data for USA BASE Map	150
5.3.2	Evaluating the Geographical Data for Pasir Gudang Map	152
5.4	Discussion	154
5.5	Summary	154

6	CONCLUSION	156
6.1	Introduction	156
6.1.1	Mobile GIS Area	158
6.1.2	Database Area	158
6.1.3	R-tree and Quadtree spatial data indexing method	159
6.1.4	QuadR-tree spatial data indexing method	160
6.1.5	Rule-based Expert Knowledge Area	161
6.1.6	Test and Development Area	161
6.2	Research Contribution	162
6.3	Advantages	162
6.4	Disadvantages	163
6.5	Future Work	164
6.6	Conclusion	164
	REFERENCES	160
	APPENDICES A – C	171-176

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Characteristics of wireless networks (Source: (Quinn et al., 2005))	23
2.2	Summary of Mobile GIS issues and problems	25
3.1	Example of R-tree and Quadtree Rule-based data set	77
3.2	Requirement for testing and experiment	86
4.1	Tables used in the Pasir Gudang map spatial database	90
4.2	BANGUNAN_ELLIPSE, BANGUNAN_POLYLINE, BANGUNAN_REGION properties	90
4.3	BANGUNAN_TEXT properties	91
4.4	JALAN_ POLYLINE properties	91
4.5	LOT_LUAR_REGION properties	91
4.6	LOT_ REGION properties	92
4.7	MINIMUM_TROUGHPUT_REGION properties	92
4.8	SEMPADAN_KAWASAN_REGION properties	93
4.9	ZONING_REGION properties	93
4.10	Tables used in the USA BASE map spatial database	94
4.11	Rule and Weight's result in Pasir Gudang map tables	111
4.12	Rule and Weight's result in USA BASE map tables	112
4.13	QuadRtree indexing selection engine result for Pasir	

	Gudang map tables	111
4.14	QuadRtree indexing selection engine result for USA BASE map tables	117
5.1	QuadRtree indexing selection engine result for Pasir Gudang map tables	151
5.2	USA BASE map experiment result Pasir Gudang map experiment result	152

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Examples of three-tier client-server architecture	21
2.2	Example of mobile GIS architecture. [Source: (Tsou, 2004)]	22
2.3	R-tree schema 1 (Guttman, 1984)	38
2.4	R-tree schema 2 (Guttman, 1984)	38
2.5	Quadtree schema	41
3.1	Research framework	71
3.2	Research methodology	72
3.3	R-tree algorithm (Guttman, 1974)	73
3.4	Quadtree algorithm (Finkel & Bentley, 1974)	74
3.5	QuadRtree selection engine algorithm	75-76
3.6	Page Automatic Selection Engine	81
3.7	Page Table	81
3.8	Page Condition	82
3.9	Implementation of Mobile GIS framework	83
3.10	Testing framework	84
3.11	Architecture of QuadRtree Selection Engine for Mobile GIS	87
4.1	Flow of QuadRtree indexing selection engine algorithm	116

4.2	Oracle Application Server architecture [Modified from (Oracle AS White Paper, 2007)]	121
5.1	Check the map	126
5.2	The map already builds in the system	126
5.3	Choose to use QuadRtree Selection Engine or not	127
5.4	Read the Database	127
5.5	Page Table	128
5.6	Page Table 2	128
5.7	Page Condition	129
5.8	R-tree Index Page	129
5.9	Page Condition 2	130
5.10	Page Condition 4	130
5.11	Page Last Table	131
5.12	Pasir Gudang map	131
5.13	Show the ZONING layer	132
5.14	Show the JALAN layer	133
5.15	Show the LOT_REGION – LOT Layer	134
5.16	Show the LOT_LUAR_REGION – LOT Layer	135
5.17	Show the MINIMUM_THROUGHPUT_REGION and SEMPADAN _KAWASAN_REGION - Default layer	136
5.18	Show the BANGUNAN_REGION and BANGUNAN_TEXT - Default Layer	137
5.19	Show the BANGUNAN_ELIPSE and BANGUNAN_POLYLINE – Default Layer	138
5.20	Show the Default Layer	139
5.21	Show the research files	140
5.22	Search function	141
5.23	Data search result	142
5.24	Specific map or nearer zoom location	143
5.25	Print the Map	144
5.26	Measure Distance	145
5.27	Create Buffer	146
5.28	Select Polygon	147

5.29	Select Within	148
5.30	USA BASE map	149
5.31	Average response time of spatial data indexes for USA BASE map	151
5.32	Average response time of spatial data indexes for Pasir Gudang Map	153

LIST OF ABBREVIATIONS

4CRS	Four-Color Raster Signature
AI	Artificial Intelligence
AIDS	Acquired Immunodeficiency Syndrome
AJAX	Asynchronous JavaScript Technology and XML
API	Application Programming Interface
AS	Application Server
CBIR	Content-Based Image Retrieval
CDMA	Code Division Multiple Access
CCAA	Computable Context-Awareness Approach
CISMeF	Catalogue and Index of French-speaking Medical Sites
DML	Data Manipulation Language
DW	Data Warehouse
FSI	Fluid-Structure Interaction
GABRIEL	Gis Activity-Based Travel Simulator
GIS	Geographic Information System
GKD	Geographic Knowledge Discovery
GPS	Global Positioning System
GSM	Global System for Mobile communication
HIV	Human Immunodeficiency Virus
HMBR	Hybrid Minimum Bounding Rectangle
HTML	Hyper Text Markup Language
HTTP	Hypertext Transfer Protocol
I/O	Input / Output

IG	Information Gain
IIS	Internet Information Services
IR	Information Retrieval
ITS	Intelligent Transformation System
JDBC	Java Database Connectivity
KBES	Knowledge Based Expert System
KML	Keyhole Markup Language
KMS	Knowledge Management Systems
LBS	Location Based Service
LOD	Level of Detail
LRS	Linear Referencing System)
MBR	Minimum Bounding Rectangle
MHF	Multilevel Hashing File
MPI	Message Passing Interface
MoGeo	Mobile Geographic Education
MVLQ	Multiversion Linear Quadtree
NSERC	Natural Sciences and Engineering Research Council
OLAP	On-Line Analytical Processing
OPMN	Oracle Process Manager and Notification Server
p-FEM	Spectral Finite Element
PC	Personal Computer
PDA	Personal Digital Assistants
PIST	Practical Index for Spatio-Temporal
POS	Part-of-Speech
PL/SQL	Procedural Language/Structured Query Language
RDBMS	Relational Database Management System
SDBMS	Spatial Data Base Management System
SISCam	Seismotectonic Information System of the Campania Region
SNDB	Simple Network Database
SOA	Service-Oriented Architecture
SOLAP	Spatial On-Line Analytical Processing
SP	Search Profile
SSL	Secure Socket Layer

SQL	Structured Query Language
STAMs	Spatio-Temporal Access Methods
TCP	Transmission Control Protocol
URL	Uniform Resource Locator
UTM	University Teknologi Malaysia
WiFi	Wireless Fidelity
WiMax	Worldwide Interoperability for Microwave Access
WLAN	Wireless Local Area Network
WMAN	Wireless Metropolitan Area Network
WPAN	Wireless Personal Area Network
WWAN	Wireless Wide Area Network
WWW	World Wide Web
XML	Extensible Markup Language

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Main research activities	170
B	List of publications	171
C	Research's poster	175

CHAPTER 1

INTRODUCTION

1.1 Introduction

Mobile GIS can be described as an extension of a Geographical Information System (GIS). Previously, GIS can only run in an office with a desktop GIS. By using mobile GIS, user can retrieve, transfer, update, manipulate, analyze and display geographic information anywhere and anytime. The standard technology integrated in Mobile GIS application are wireless network for internet transfer and data access, mobile device to run GIS application everywhere and Global Positioning System (GPS) to detect the location.

Over the last few years, Mobile GIS applications and technological trends have a rapid development. The success and emergence of the WWW (World Wide Web) and internet also support its rapid advancement. Geo-information technology has emerged from mainframe computers to stand alone desktop computer GIS, local networking GIS, web GIS and the latest is Mobile GIS where map and information

are run and displayed on small mobile devices such as Mobile Phones and Personal Digital Assistants (PDA) (Rajinder, 2004).

Internet as telecommunication network over the world can be used for transferring geographical data. The integration of the internet and GIS technologies also known as internet GIS can support the demand for geographical data access and transfer (Peng & Tsou, 2003). Additionally, internet can be used for communication data between client and server. By using Mobile GIS, field data collection can be settled and sent to the server for further processing and those processes are simpler. Furthermore, client can access the information needed to enhance the collection of geographical data.

Rapid improvement in the Mobile GIS technology can solve mobile application device problems such as its small bandwidth, limitation of application capability, color resolution and small screen display (Vckovski, 1999). Recent developments of internet and Mobile GIS technology enable process of spatial data transferring, collection, processing and dissemination with large amount of geographical data (Kraak, 2002).

Indexing is one of database optimization processes which can be created using one or more database table columns to provide the foundation of rapid searching and efficient access of ordered records. Spatial indexing has a great methodology for managing records and it is identified based on its organization with a place. Some of the records are strongly connected to a place. Like other structures of indexing, geographical indexing may be merged with other indices. The difference is that spatial index has particular access process to retrieve spatial data from within the data-store and to optimize spatial queries by spatial databases.

This research attempts to provide a suitable spatial data indexing method which can reduce time of spatial data processing in Mobile GIS technology, and it attempts to provide a tuning method for spatial data indexing. The last stage is developing a web based application that can run in any Mobile GIS application to show a map. This research will be helpful in all areas that use mobile GIS applications to make decisions in the field.

1.2 Problem Background

Previously, data collection and editing process in the field take a lot of time and the result is susceptible to some errors. GIS users must visit the field to take the geographical data in the structure of paper maps. Then they carry out field edit using draft and notes on paper maps and structure. After getting geographical data, processing of field edits in the office must be interpreted and manually entered into spatial database. Consequently, geographical data is rarely accurate and up-to-date as it could have been.

With the rapid developments on Mobile GIS, now GIS can be practically used in some devices such as compact digital maps, laptop (mobile computer), PDA, etc. This new GIS technology enables companies or GIS users to get real time geographical information, much faster data update to database and application, efficient analysis, geographical data display and simpler decision making in the field.

This research deals with the development in Mobile GIS technology. In the database main area of Mobile GIS technology, the majority of latest issues and problems come from network, access, system and application, and design. In the network area there are many issues and problems on network transportation (Kwan & Casas, 2006), and bandwidth of the network transmission (Qin & Li, 2006). In the access area, the issues and problems usually come from limited computer access (Hinze et al., 2006), sensor on the information (Malek et al., 2007), query and target objects (Feng et al., 2007), and location service (Timpf, 2006). For system and application area, the issues and problems usually came from GIScience (Mount et al., 2007), Location Based Service (LBS) (Ahas et al., 2007; Min et al., 2006), map (Sarjakoski, 2007; Mwambi & Zuma, 2007), mobile devices (Cao et al., 2007), Intelligent Transformation System (ITS) (Lu, 2006), web application (Cao et al., 2007), and water management (Minor et al., 2007). Finally, in the design area, the issues and problems usually came from kinetic data structures (Blunck et al., 2006), design management (Nappi et al., 2007), large volume of geo-based model and multi-stage graphic pipeline (Coors et al., 1999; Losa & Cervella, 1999), algorithm design (Karnatak et al., 2007), and traditional techniques design (Burigat & Chittaro, 2007).

Nowadays the use of internet increases significantly. It makes internet system management more complicated and difficult. Currently, most of the actions lead to increase the mobile service presented by the internet. However, this approach produces many network problems. Previously, many improvements are increasing the storage on the web server through spreading out of the communication bandwidth. Nevertheless, this former improvement takes very high cost and the bandwidth development is not appropriate in a mobile environment.

The major concern of most wireless technology is the overloading of servers because of system bottleneck phenomenon. Mobile GIS applications use wireless technology for transferring process and retrieving data, besides needs concentrating

to explore and solve that problem. There are four main areas affecting system bottleneck phenomenon; database, network, application server and web server. The major problem for system bottleneck phenomenon originates from the database (Kwan & Shi, 2002). Infrastructure and architecture exploration are the main part in mobile computing research to solve system bottleneck problem. This has been done by developing the third generation mobile systems or resolving cache management of the database. Thus optimizing the existing system such as fine tuning database is an important step to enhance the overall performance.

Database research can be grouped into two major areas, they are database design and database access. In the design database there are many issues and problems with modeling spatio-temporal database area (Praing & Schneider, 2007), information and operating database area (Kim et al., 2006), geo ontologies in geo databases area (Baglioni et al., 2007), and spatial-network constrained moving objects area (Lu et al., 2007). In another area, which is in the access database there are many issues and problems in the access control in geographic databases area (Sasaoka & Medeiros, 2006), access control in the mobile crisis management systems area (Luyten, 2006), Data Warehouse (DW) and On-Line Analytical Processing (OLAP) area (Rivest et al., 2001), spatial data sharing, data warehousing and database federation area (Yeung & Hall, 2007), spatial database systems area (Yeung & Hall, 2007), SOLAP (Spatial OLAP) area (Bédard et al., 2007), spatial network databases area (Chang et al., 2006), spatial-temporal databases area (Azevedo, 2007), spatial database cluster and storage area (You et al., 2007), indexing technique for historical Spatio-Temporal point data area (Botea et al., 2007), spatial index and hashing technique area (Kim et al., 2005).

Data model separation for future movements is one of the problems in spatio-temporal database modeling area. The problems are the lack of generic data model for future movements also separation of past and future movement models for moving objects. These problems have been solved using design of spatio-temporal

predicates on Balloon objects. Balloon objects is the model which considers both the past and the future movements of moving objects while preserving their temporal consistency. It based on a new set of spatio-temporal data types and operations which considers both past and future movements of moving objects while preserving their temporal consistency approaches. This subject area has some issues for further research by considering chances quantification in which relationship between balloon objects which is composed of sequence of certain and uncertain relationship between its parts can occur (Praing & Schneider, 2007).

Quantity and quality data limitation in highway database is a problem in information and operating database area. Highways are constructed and managed by various authorities. The facilities along it have individual specifications. Therefore, obtaining detail information about the facilities and equality of format information is crucial in operating databases of highways and their facilities. This problem has been solved using mobile mapping system approach for fast and economic acquisition of qualitative information of highways and its facilities. However, this subject still has some issues for further research which is obtaining detail information about the facilities. Besides, equality of information format is critical issue in operating databases of highways and their facilities (Kim et al., 2006).

There are some geo ontological problems in geo databases area, i.e. complexity, high cost and time consuming task. Those problems can lead to mistakes and information missing to construct ontology which can be constructed manually from data analysis of database structure and table contents. But those problems can be answered by describing an approach to extract geospatial ontology from geographical data stored in spatial databases. Indeed, this subject needs further research to investigate how to exploit the enriched ontology for semantic integration of geo databases (Baglioni et al., 2007).

Range monitoring of mobile object in network distance appears as problem in spatial-network constrained moving objects area. Furthermore, the ability to continuously monitor mobile objects position is important in many applications. This problem has been solved by proposing an architecture where mobile clients and central server can share computation to obtain scalability by utilizing the capabilities of the clients. The proposed method can improve query maintenance and synchronization by recognizing the overlapping queries. Further research that concern on spatial-network constrained moving objects, monitoring free-moving objects is still needed in this area (Lu et al., 2007).

Determining when users or applications can access stored data and what kind of access they are allowed are some of the problems in the access control on geographic databases area. Verifying the type of store access data for applications and users is one of the problems in access control database. This problem has been solved with extending classical models and mechanisms to the spatial context. Indeed, this subject area still has some issues for further research that need to concerns the incorporation of nested permissions, conflicts among their rules to maintain rule consistency, and the performance concerns impact of checking algorithms (Sasaoka & Medeiros, 2006).

A firefighter emergency mission is very important to get the trustworthy overview of each member in fire brigade complete situation. Those are some of the problems in the mobile crisis management systems area. This problem has been solved with reporting the design and development of a system to support a fire brigade on site with a set of mobile services that offers a role-based focus + context user interface. Further research that need to add context-awareness without changing the structure or navigation of the user interface, but merely parts of the presentation is still needed in this area (Luyten, 2006).

The system that can't store and manipulate data is one of the problems in the Data Warehouse (DW) and On-Line Analytical Processing (OLAP) area. Since it is estimated that about 80% of data stored in databases has a spatial or location component (Rivest et al., 2001), location dimensions have been widely integrated in DWs and in OLAP systems. This problem has been solved by proposing the transformation of a conceptual schema based on the MultiDimER constructs to an object-relational schema. They based our mapping on the SQL: 2003 and SQL/MM standards giving examples of commercial implementation using Oracle 10g with its spatial extension. However, this subject area still has some issues for further research that the additional programming effort is required to ensure the equivalence between conceptual and logical schemas (Malinowski & Zimányi, 2006).

Spatial data sharing is one of the problems in the spatial data sharing, data warehousing and database federation area. Spatial data sharing is no longer perceived simply as the selling of maps or the occasional exchange of data among individuals or organizations. Instead, it has become both a commercial business and a standard practice in modern data processing that transcends different application and technical domains. This problem has been solved using approaches in semantic modeling within the many database communities that exist even within the global spatial data domain. Indeed, this subject area still has some issues for further research, as the increasing use of standards has gradually eliminated many of the difficulties resulting from incompatibility of data structure and syntax, spatial data sharing at present is predominantly concerned with issues of access (including policy, legal liability, discovery and dissemination) and collaborated applications (semantics and interfaces), rather than with the technical exchange of data between disparate data sets as in the past (Yeung & Hall, 2007).

How to support basic needs in spatial data capture, provide easily understandable spatial data structures models, and facilitate cartographic presentation are some of the problems in the spatial database systems area. Conventionally, the

spatial information industry sought to support basic needs in spatial data capture, provide easily understandable spatial data structures and models, and facilitate cartographic presentation of the results of spatial analysis and map-based manipulation of data. This problem has been solved with identifies the major current trends in spatial design database and implementation, review emerging concepts and techniques that are shaping the trends of spatial database systems from the perspectives of technology, data, application and people, and discusses the implications of these trends for the spatial database research community. Indeed, this subject area still has some issues for further research. Building spatial data and a data-centric environment that places emphasis on the need to understand spatial databases and their management rather than focus on technical aspects of the spatial data themselves will characterize the future spatial information industry (Yeung & Hall, 2007).

Slow down query and cryptic data structures are some of the problems in the SOLAP (Spatial OLAP) main subject. Geographic Knowledge Discovery (GKD) requires systems that support interactive exploration of data without being slowed down by the intricacies of a SQL (Structured Query Language) type query language and cryptic data structures. This problem has been solved using a Hypermedia SOLAP method. GKD requires comparing maps of different phenomena or epochs, to dig into these maps to obtain detailed information, to roll-up data for more global information and to synchronize maps with tables and charts. However, this subject area still has some issues for further research. While such developments will enhance the experience of the user with the system, important questions remain with respect to the competing objectives of providing documents to fulfill the requirements of specific users and concomitantly respecting privacy concerns. Future works related to the NSERC (Natural Sciences and Engineering Research Council) Industrial Research Chair will take such considerations into account and will address some technological and legal issues raised by the distribution and the sharing of such Hypermedia and SOLAP information over networks. As it has designed and developed the SOLAP technology used for the project (Kheops, 2005). It will

continue improving this technology, including its enrichment with other types of data such as hypermedia (Bédard et al., 2007).

Spatial network databases that consider Euclidean spaces in spatial databases, where the distance between two objects is determined by the ideal shortest path connecting them are some of the problems in the spatial network database area. Most of existing work in spatial databases considers Euclidean spaces, where the distance between two objects is determined by the ideal shortest path connecting them (Shekhar et al., 1999). This problem has been solved with designed the architecture of disk-based data structures for SNDB (Simple Network Database. Further research that required to study on e-distance join and closest-pairs query processing algorithms for SNDB based on their range and k-NN query processing algorithms is still needed in this area (Chang et al., 2006).

How to process queries efficiently so that the user does not have to wait a long time to get an answer is one of the problems in the spatial-temporal databases main subject. This problem has been solved using raster signatures method, approximate the query processing in spatial databases. They extended the proposals of using Four-Color Raster Signature (4CRS) (Zimbrão & Souza, 1998) for fast and approximate processing of queries over polygon datasets. Indeed, this subject area still has some issues for further research. Providing a short time answer to queries becomes a bigger challenge in spatial database area, where the data usually have high complexity and are available in huge amounts (Azevedo, 2007).

Huge amount of data in sensor networks that is collected by millions of sensors and small mobile devices need to be processed fast. In addition, the database requires to always acting in response. This is one of the problems in spatial database cluster and storage area. This problem has been solved using the cluster recovery of

spatial database cluster method. The proposed method has the cluster log that need to write in fail node case to improve the update transaction. Further research that small mobile devices need to be processed fast in sensor networks is still needed in this area, because a huge amount of data is collected by millions of sensors. Database also should be able to response for any requirement (You et al., 2007).

Relational Database Management System (RDBMS) support for spatio-temporal data is limited and inadequate, most existing spatio-temporal indices cannot be readily integrated into existing RDBMSs. This is one of the problems in the indexing technique for historical Spatio-Temporal point data main subject. The need for Spatio-Temporal Access Methods (STAMs) integrated within a RDBMS has become increasingly apparent. This problem has been solved with proposing a Practical Index for Spatio-Temporal (PIST) data, an indexing technique, rather than a new indexing structure, for historical spatio-temporal data points that can be fully integrated within existing RDBMSs. However, this subject area still has some issues for further research that must increase the number of indexed temporal ranges and hence the number of records in the database (Botea et al., 2007).

Limited memory and a low computational capacity in the mobile devices are some of the problems in the spatial index and hashing technique area. The volume of spatial data and the computational cost of spatial operations are very tremendous, but on the other hand the mobile devices own a limited memory and a low computational capacity than the Personal Computer (PC). Therefore, a spatial index for the mobile devices should be small and achieve good filtering efficiency as well. This problem has been solved using a spatial index called MHF (Multilevel Hashing File) method for the mobile map service. The construction's storage utilization of MHF is using the simple hashing technique to improve the searching performance. Thus designs a compression scheme of MBR (Minimum Bounding Rectangle) called HMBR (Hybrid MBR). Further research that the index is expected to be useful for mobile map service, ITS (Intelligent Transportation System), LBS (Location Based Service)

to have been increasingly studied recently is still needed in this area (Kim et al., 2005).

Database is an essential component in GIS and no doubt, a poor access is a burden to the performance. Concentrating on optimizing the database will give better GIS application performance. Since the majority of latest issues and problems come from design database area, focusing on design database area that can be solved using spatial data indexing method is an essential matter. The development of spatial data indexing approach, including tuning spatial data indexing itself for Mobile GIS technology, is one of good steps. Spatial index is very important in GIS because it is used by spatial databases to optimize spatial queries that can fasten transferring process and spatial data retrieval through Mobile GIS network.

R-tree and Quadtree indexes that use extensive framework are the best spatial data indexing methods among any other existing spatial indexing methods for low-dimensional spatial data (Kothuri et al, 2002). For queries processing, R-tree approach may be more efficient due to better maintenance of spatial immediacy, but may be slow in updating or index creating and implementation of own concurrency protocols on top of table-level concurrency mechanisms, since R-tree is built logically as a tree and physically using tables inside the database and search involves recursive SQL for traversing tree from root to relevant leaves. Linear Quad-tree results in simpler index creation, faster update and inherit configuration in B-tree concurrency control protocols, since those indexes compute tile approximations for geometries and use existing Btree indexes for performing spatial search and other DML operations.

Most of previous researchers described above have experimented in changing the structure of R-tree and Quadtree spatial data indexing method that could give

better performance. However it still leaves some issues and problems that need to be solved. One of the most common issues and problems is that the method is only applicable to some of applications such as data arrangement, but it needs speed improvement in transfer process and data retrieval. This research gives different methodology that concentrates on fine tuning of a spatial database system using R-tree and Quadtree spatial data indexing method, without changing the structure of those spatial data indexing method. This research proposes QuadR-tree, a selection engine to choose between R-tree and Quadtree spatial data indexing method. Consequently, there are two spatial indexes in a single spatial database system which combines R-tree and Quadtree. Most of common issues and problems above, that each one only optimal in different condition can be solved with this research proposed method. The proposed method read the input condition to be matched with the knowledge in the rule base data set, which is dynamic and can be updated again. Thus, every different map condition and application still can be run with optimum performance if we apply our proposed method.

Previous research (Chen et al, 2003 and Francis et al., 2008) that delivers similar methodology and contributes improvement to this research is Hybrid Quadtree and R-tree spatial data indexing method. QR-tree presenting a quick speed spatial indexing structure based on Quadtree and R-tree. It carries out data space with the space level partition strategy of Quadtree multistage partition and uses different R-tree index space object for each partition subspace. The research indicates that although QR-tree always demands more storage space than R-tree, it gains better performance in insertion, deletion, and especially searching. The result also showed that the more amounts of spatial data, the less cost and the better performance of QR-tree. In the other word, for a very large spatial database, QR-tree possesses more superior than R-tree (Chen et al, 2003). Another similar methodology is a scalable constraint-based Q-hash indexing for moving objects (Francis et al., 2008). These previous researches combine the algorithm structure of R-tree and Quadtree to become a new structure of spatial data indexing method. However these previous

researches have some problems that need a big storage, besides it is only better in some ranges of data as well as moving object environment.

To summarize this problem background, firstly it can be seen that the majority latest issues and problems in Mobile GIS come from database area. Mobile GIS needs wireless technology, but a problem comes from system bottleneck. According to Kim and Shi research, the main problem in system bottleneck is because of database side (Kim & Shi, 2002). Database area can be grouped into two branches, i.e database designs and access database. Due to the majority latest issues and problems come from design database, our research tries to focus on this area, by choosing R-tree and Quadtree spatial data indexing method, since both are the best spatial data indexing method for mobile GIS technology. Secondly, we find the nearest research that delivered similar methodology which brings new improvement for our research.

1.3 Problem Statement

Generally, a problem in Mobile GIS lies in transfer process and spatial data retrieval using wireless technology that is still not efficient. To improve that process, therefore some optimization in spatial database system is a mandatory thing. One of the ways to optimize process of transferring and retrieving data in spatial database system through Mobile GIS network is spatial data indexing approach. The best spatial data indexing methods are R-tree and Quadtree. Each of those methods has different advantages and disadvantages based on the requirement of the applications and type of data; if Quadtree and R-tree are used together for data indexing in a

single spatial database system, the database can be optimized with the appropriate spatial data indexing method and contribute to improve spatial data transferring speed. Currently, there is no selection algorithm to select between those of spatial data indexing methods.

1.4 Goal and Objectives

The goal of this research is to provide new method of tuning spatial database for improve speed of data manipulation by developing selection engine. The objectives in order to realize this goal are:

- i. To define parameter of spatial data optimization based on Quad-tree and R-tree for tuning method.
- ii. To design selection algorithm using rule based expert knowledge for develop selection engine of tuning method.
- iii. To develop selection engine for spatial data optimization in GIS application to validate and testing the proposed approach.

1.5 Scope of the Study

The scope of the research includes:

- i. The first scope is defining the selection parameter. It needs to understand the requirement of applications and type of data. The selecting parameter is based on the advantages and disadvantages of R-tree and Quadtree spatial data indexes, in regards of this research only proposed the combination of using those spatial data indices.
- ii. The second scope is developing selection engine. It needs to understand some of the selection algorithms for selecting only two objects. The selection algorithm is based on the knowledge of R-tree and Quadtree spatial data indexes, which means it only needs to explore based on the ruled based selection method in the knowledge dataset.
- iii. The third scope is developing prototype of Mobile GIS application for testing and validation. It needs to understand the applications that can be run effectively in Mobile GIS application. Web based application can be run in any mobile applications using browser without require specific program.

1.6 Expected Contribution and Summary

This research is expected to provide new paradigm in combining the used of more than one spatial data indexes without changing the structure of those spatial data indexes. This research is also expected to propose selection algorithm in R-tree – Quadtree spatial data indexes and Mobile GIS area using Rule Based Knowledge Expert. This chapter starts from introduction, problem background and problem statement in Mobile GIS and spatial data indexes algorithm, specifically R-tree and

Quadtree spatial data indexes. The goals and objectives with the limitation of scope covered under this research have also been described. Finally, this research ends with expected contribution and summary.

REFERENCES

- Ahas, R., Laineste, J., Aasa, A., Mark, U. (2007). The Spatial Accuracy of Mobile Positioning: Some experiences with Geographical Studies in Estonia. *Location Based Services and Tele Cartography*, 445-460.
- Ahas, R., & Mark, Ü. (2005). *Location based services – new challenges for planning and public administration Futures*, 37(6), 547-561.
- Adams, P. M., Ashwell, G. W. B., Baxter, R. (2003). *Location-based services – an overview of standards*. *BT Technology Journal*, 21(1), 34–43.
- Allen, J. F. (1983). *Maintaining Knowledge about Temporal Intervals*. *Communications of the ACM*, 26(11), 832-843.
- Amato, A., & Montone, P. (1997). Present-day stress field and active tectonics in southern peninsular Italy. *Geophys J Int* 130, 519–534.
- An, N., Kothuri, R. K. V., Ravada, S. (2003). Improving Performance with Bulk-Inserts in Oracle R-Trees. *Proceedings 2003 VLDB Conference*, 2003, pp 948-951.
- Anderson, R. C. (1984). Role of reader's schema in comprehension, learning and memory. In R. Anderson, J. Osborn, & R. Tierney (eds), *Learning to read in American schools: Basal readers and content texts*. Hillsdale, NJ: Lawrence Erlbaum Associates.
- Anderson, R. M., & May, R. M. (1991). *Infectious Diseases of Humans*. Oxford, UK: Oxford University Press.
- Armstrong, M. P., Bennett, D. A. (2005). A manifesto on mobile computing in geographic education. *The Professional Geographer*, vol 57(4), 506-515.

- Asher, N., & Vieu, L. (1995). *Towards a geometry of common sense: a semantics and a complete axiomatisation of mereotopology*, Proc. of IJCAI95.
- Azevedo, L. G., Zimbrão, G., Souza, J. M. (2007). Approximate Query Processing in Spatial Databases Using Raster Signatures. *Advances in Geoinformatics*, 69-86.
- Baglioni, M., Masserotti, M. V., Renso, C., Spinsanti, L. (2007). Building Geospatial Ontologies from Geographical Databases. *GeoSpatial Semantics*, 195-209.
- Becker, L., Blunck, H., Hinrichs, H. K., Vahrenhold, J. (2004). A framework for representing moving objects. In: *Proc 15th Int Conf Database and Expert Systems Applications (= LNCS 3180)*, 854–863.
- Becker, L., Voigtmann, A., Hinrichs, K. H. (1996). Developing Applications with the Object Oriented GIS-Kernel GOODAC. In: *Proc 7th Int Symp Spatial Data Handling vol I:5A1-5A18*.
- Bédard, Y., Proulx, M. J., Rivest, S., Badard, T. (2007). Merging Hypermedia GIS with Spatial On-Line Analytical Processing: Towards Hypermedia SOLAP. *Geographic Hypermedia*, 167-187.
- Bentley, J. L. 1990. K-d Trees for Semidynamic Point Sets. SCG '90: *Proc. 6th Annual Symposium on Computational Geometry (1990)*, 187–197.
- Berg, M., Kreveld, M., Overmars, M., Schwarzkopf, O. (1997). Computational Geometry: *Algorithms and Applications*. Springer-Verlag: ISBN 3-540-65620-0.
- Blunck, H., Hinrichs, K., Sondern, J., Vahrenhold, J. (2006). Modeling and Engineering Algorithms for Mobile Data. *Progress in Spatial Data Handling*, 61-77.
- Born, M. (1949). Natural Philosophy of Cause and Chance, *Dover Publ., NY*.
- Botea, V., Mallett, D., Nascimento, M. A., Sander, J. (2007). *PIST: An Efficient and Practical Indexing Technique for Historical Spatio-Temporal Point Data*.
- Brauer, F. (2005). The Kermack-Mackendrick epidemic model revisited. *Mathematical Biosciences*, 198, 119-131.
- Burigat, S., & Chittaro, L. (2007). Geographical Data Visualization on Mobile Devices for User's Navigation and Decision Support Activities. *Spatial Data on the Web*, 261-284.

- Caduff, D. (2002). *Sketch-Based Queries in Mobile GIS-Environments*. Master Thesis, Maine University.
- Caduff, D. (2002). *Sketch-Based Queries in Mobile GIS-Environments*. Master Thesis, Maine University.
- Cao, Y., Klamma, R., Srirama, S., Wang, S. (2007). The Mobile Interfaces for Geo-hypermedia Databases. *On the Move to Meaningful Internet Systems 2007: OTM 2007 Workshops*, 417-426.
- Chan, E. P. F., & Chow, K. K. W. (2002). On multi-scale display of geometric objects. *Data & Knowledge Engineering, Volume 40, Issue 1*, January 2002, pp 91-119.
- Chen, Y. F, Yong, Z. H., Guo, W., Zhou, D. R. (2003). QR-tree: a hybrid spatial index structure. *Machine Learning and Cybernetics, 2003 International Conference on Volume 1*, Issue, 2-5 Nov. 2003 Page(s): 459 - 463 Vol.1
- Chang, C. Y., Maciejewski, A. A., Balakrishnan, V., Roberts, R. G., Saitwal, K. (2006). *Quadtree-based eigen decomposition for pose estimation in the presence of occlusion and background clutter*.
- Chang, J. W., Kim, Y. K., Kim, S. M., Kim, Y. C. (2006). New Query Processing Algorithms for Range and k-NN Search in Spatial Network Databases. *Advances in Conceptual Modeling - Theory and Practice*, 130-139.
- Cheng, S. W. & Lee, K. H. (2008). Quadtree Decomposition, Steiner Triangulation, and Ray Shooting. *Algorithms and Computation*, 368-377.
- Chi, M. T. H., Feltovich, P. J., Glaser, R. (1981). Categorization and representation of physics problems by experts and novices. *Cognitive Science*, 5, 121-152.
- Chon, H., Agrawal, D. Abbadi, A. E. (2001). Storage and Retrieval of Moving Objects. *Proceeding of International Conference on Mobile Data Management*.
- Chow, P. K. O., Yeung, D. S. (1995). Multidimensional Knowledge Structure. *Expert Systems with Applications*. Vol. 9, No. 2, 1995, pp. 177-187.
- Coors, V., Jasnoch, U., Jung, V. (1999). Using the Virtual Table as an interaction platform for collaborative urban planning. *Computers & Graphics*, 23, 487-496.
- Cowen, D. J. (1988). Gis versus cad versus dbms: what are the differences? *Photogrammetric Engineering and Remote Sensing*, 54:1551-4.

- Daley, D. J., & Gani, J. (1999). Epidemic Modelling. An Introduction. *Cambridge Studies in mathematical Biology*. Cambridge, UK: Cambridge University Press.
- Davey, B. A., & Priestly, H. A. (1990). Introduction to Lattices and Order. *Cambridge University Press, UK*.
- Detyniecki, M., Freeman. (2007). Adaptive Discovery of Indexing Rules for Video. *Lecture Notes in Computer Science*. Springer Berlin / Heidelberg.
- Durkin, J. (1994). *Expert Systems: Design and Development*. Prentice Hall Inc.
- Egan, F. G. (2003). *Practical RF System Design*. Wiley-IEEE.
- Ellis, C. S. (1999). The case for higher-level power management. *Proc. of 7th IEEE Workshop on Hot Topics in Operating System, Rio Rico*.
- Eppstein, D., Michael, T., Goodrich, Jonathan, Z., S. (2005). A Simple Dynamic Data Structure For Multidimensional Data. *Univ. of California, Irvine Donald Bren School of Information and Computer Sciences*.
- Ervin, S. M., & Hasbrouck, H. H. (2001). *Landscape Modeling: Digital Techniques for Landscape Visualiztion*, McGraw-Hill, 289p.
- Feng, J., Wu L., Zhu Y., Mukai, N., Watanabe, T. (2007). Continuous k-Nearest Neighbor Search under Mobile Environment. *Advances in Data and Web Management*, 566-573.
- Finkel, R., & Bentley, J. L. (1974). *Quad Trees: A Data Structure for Retrieval on Composite Keys*. *Acta Informatica* 4 (1): 1- 9.
- Flinn, J., M., S. (1999). Energy-aware Adaptation for Mobile Application. *Proc. of Symposium on Operating Systems Principals*.
- Forman, G. H., & Zahorjan, J. (1994). *The Challenges of Mobile Computing*. IEEE Computer, 27(4), 38-47.
- Francis, Madria, M., Sabharwala C. (2008). A scalable constraint-based Q-hash indexing for moving objects. *Information Sciences: an International Journal on Volume 178 , Issue 6*. ISSN:0020-0255.
- Geller, S., Talke, J., Krafczyk, M. (2007). Lattice-Boltzmann Method on Quadtree-Type Grids for Fluid Structure Interaction. *Fluid-Structure Interaction*, 270-293.

- Grbovic, J. P., Fagg, G. E., Angskun, T., Bosilca, G., Dongarra, J. J. (2006). MPI Collective Algorithm Selection and Quadtree Encoding. *Recent Advances in Parallel Virtual Machine and Message Passing Interface*, 40-48.
- Guttman, A. (1984). R-Trees: A Dynamic Index Structure for Spatial Searching. *Proc. 1984 ACM SIGMOD International Conference on Management of Data*, pp. 47- 57.
- Hinze, A., Gao, X., Bainbridge, D. (2006). The TIP/Greenstone Bridge: A Service for Mobile Location-Based Access to Digital Libraries. *Research and Advanced Technology for Digital Libraries*, 99-110.
- K. V. Ravi Kanth, Siva Ravada, J. Sharma, J. Banerjee (1999). *Indexing medium-dimensionality data in oracle*. In Proc. ACM SIGMOD Int. Conf. on Management of Data.
- K. V. Ravi Kanth & Siva Ravada (2001). Efficient processing of large spatial queries using interior approximations. *In Symposium on Spatial and Temporal Databases (SSTD)*.
- Karnatak, H. C., Saran, S., Bhatia, K., Roy, P. S. (2007). *Multicriteria Spatial Decision Analysis in Web GIS Environment*.
- Kheops (2005). *JMap spatial OLAP*. <http://www.kheops-tech.com/en/jmap/solap.jsp>.
- Kothuri, R. K. V., Ravada, S., Abugov, D. (2002). Quadtree and R-tree Indexes in Oracle Spatial: A comparison using GIS Data. *ACM SIGMOD 2002 June 4-6, Madison, Wisconsin, USA*.
- Kim, J. H., Jeong, D. H., Kim, B. G. (2006). Photograph Database for Highway Facility Management in Mobile Mapping System. *Computational Science and Its Applications - ICCSA 2006*, 996-1002.
- Kim, S. Y., & Lee, K. (2007). Design and Implementation of Mobile 3D City, Landscape Authoring/Rendering System. *Innovations in 3D Geo Information Systems*, 439-446.
- Kim, J. D., Moon, S. H., Choi, J. O. (2005). A Spatial Index Using MBR Compression and Hashing Technique for Mobile Map Service. *Database Systems for Advanced Applications*, 625-636.
- Kraak, M. J. (2002). Current trends in visualisation of geographic data with special reference to cartography: Invited paper. *In Proceedings of the XXIIth INCA*

- Congress 2002, Indian National Cartographic Association: Convergence of Imagery Information and Maps*, volume 22, 319–324.
- Kwan, K., & Shi, W. (2002). *A Study of Dynamic Database in Mobile GIS*.
- Kwan, M. P., & Casas, I. (2006). GABRIEL: Gis Activity-Based tRavel sImuLator. *Activity Scheduling in the Presence of Real-Time Information. GeoInformatica*, 469-493.
- Lee, D. H., & Kim, H. J. (2001). A fast content-based indexing and retrieval technique by the shape information in large image database. *Journal of Systems and Software*, Volume 56, Issue 2, 1 March 2001, pp 165-182.
- Lee, M. L., Hsu, W., Jensen, C. S., Cui, B., Teo, K. L. (2003). Supporting Frequent Updates in R-Trees: A Bottom-Up Approach. *Proceedings 2003 VLDB Conference, 2003*, pp 608-619.
- Lee, T., Moon, B., Lee, S. (2006). Bulk insertion for R-trees by seeded clustering. *Data & Knowledge Engineering*, Volume 59, Issue 1, October 2006, pp 86-106.
- Liu, C. M., & Fu, S. Y. (2008). Effective protocols for kNN search on broadcast multi-dimensional index trees. *Information Systems*, Volume 33, Issue 1, March 2008, pp 18-35.
- Losa, A., & Cervella, B. (1999). *3D Topological modeling and visualization for 3D GIS*. *Computers & Graphics*, 23, 469-478.
- Luyten, K., Winters, F., Coninx, K., Naudts, D., Moerman, I. (2006). A Situation-Aware Mobile System to Support Fire Brigades in Emergency Situations. *On the Move to Meaningful Internet Systems 2006: OTM 2006 Workshops*, 1966-1975.
- Lu, H., Huang, Z., Jensen, C. S., Xu, L. (2007). Distributed, Concurrent Range Monitoring of Spatial-Network Constrained Mobile Objects. *Advances in Spatial and Temporal Databases*, 403-422.
- Lu, X. (2006). GIS-T Web Services: A New Design Model for Developing GIS Customized ITS Application Systems. *Computational Science and Its Applications - ICCSA 2006*, 875-884.
- Malek, M. R. (2004). A Logic-Based Framework for Qualitative Spatial Reasoning in Mobile GIS Environment with Applications to Navigations. *In: Ferscha*,

- A., Hoertner, H., Kotsi, G. (Ed.s) *Advances in Pervasive Computing, Austrian Computer Society*.
- Malek, M. R. (2004). A Logic-Based Framework for Qualitative Spatial Reasoning in Mobile GIS Environment. *Lecture Notes in Artificial Intelligence*, 3066, 418-426.
- Malek, M., Frank, A., Delavar, M. (2007). A Logic-Based Foundation for Spatial Relationships in Mobile GIS Environment. *Location Based Services and TeleCartography*, 193-204.
- Malinowski, E., & Zimányi, E. (2006). *Logical Representation of a Conceptual Model for Spatial Data Warehouses*. *GeoInformatica*, 431-475.
- Mannings, R., & Pearson, I. (2003). 'Virtual Air' – A novel way to consider and exploit LBS with AR. *Journal of the Communications Network*, 2(1), 29–33.
- Map Guide White Paper (2008). *Map Guide GIS application, 2008 Release*.
- Markl, V. (1999). *MISTRAL: Processing Relational Queries using a Multidimensional Access Technique*. Doctoral Thesis University of Munich, Germany.
- Mensah, E. (2007). *Designing a Prototype Mobile GIS to Support Cadastral Data Collection in Ghana*, 44.
- Milano, G., Digiovambattista, R., Alessio, G. (1999). *Earthquake swarms in the Southern Apennines chain (Italy): the 1997 seismic sequence in the Sannio-Matese mountains*. *Tectonophysics*, 306, 57–78.
- Milano, G., Digiovambattista, R., Ventura, G. (2005). *The 2001 seismic activity near Isernia (Italy): implications for the seismotectonics of the Central-Southern Apennines*. *Tectonophysics*, 401, 167–178.
- Min, K. W., Kim, J. W., Park, J. H. (2006). Optimal Route Determination Technology Based on Trajectory Querying Moving Object Database. *Database and Expert Systems Applications*, 666-675.
- Minor, T. B., Russel, C. E., Mizell, S. A. (2007). *Development of a GIS-based model for extrapolating mesoscale groundwater recharge estimates using integrated geospatial data sets*. *Hydrogeology Journal*, 183-195.
- Mir, Z. H. & Ko, Y. B. (2006). A Quadtree-Based Data Dissemination Protocol for Wireless Sensor Networks with Mobile Sinks. *Personal Wireless Communications*, 447-458.

- Mir, Z. H. & Ko, Y. B. (2007). A quadtree-based hierarchical data dissemination for mobile sensor networks. *Telecommunication Systems*, 117-128.
- Morales, G. J. M. (2004). *Model-driven design of Geo-information services*. PhD thesis, ITC, Enschede, The Netherlands.
- Morton, G. M. (1996). A computer Oriented Geodetic Data Base; and a New Technique in File Sequencing. *Technical Report, IBM Ltd. Ottawa, Canada*.
- Mount, J., Bennet, D., Armstrong, M. (2007). Mobile Geographic Education: The MoGeo System. *Geographic Hypermedia*, 447-464.
- Mwambi, H., & Zuma, K. (2007). Mapping and Modeling Disease Risk among Mobile Populations. *Population Mobility and Infectious Disease*, 244-266.
- Nappi, R., Ventura, G., Vilardo, G. (2004). WEB based GIS for seismotectonic risk assessment. *Abstract for 32 International Geological Congress, Firenze*, 20-28.
- Nappi, R., Alessio, G., Bronzino, G., Terranova, C., Vilardo, G. (2007). *Contribution of the SISCam Web-based GIS to the seismotectonic study of Campania (Southern Apennines): an example of application to the Sannio-area*. *Natural Hazards*, 73-85.
- Norman, C. & Lesser, V. (1994). The Evolution of Blackboard Control Architectures. *Expert Systems with Applications*, Vol. 7, No. 1, 1994, pp. 1-30.
- Oracle Spatial 10g White Paper (2006). *Oracle Spatial Quadtree Indexing, 10g Release 1 (10.1)*.
- Oracle Application Server 10g White Paper (2007). *Oracle Application Server 10g*.
- Peng, Z. R., & Tsou, M. H. (2003). *Internet GIS: Distributed Geographic Information Services for the Internet and Wireless Network*. John Wiley and Sons Inc.
- Praing, R., & Schneider, M. (2007). Advances in Conceptual Modeling – Foundations and Applications. *Modeling Historical and Future Spatio-temporal Relationships of Moving Objects in Databases*, 318-327.
- Preparata, Franco, P., Shamos, Ian, M. (1985). *Computational Geometry: An Introduction*. Springer-Verlag: ISBN 3-540- 96131-3.
- Qin, G., & Li, Q. (2006). An Information Integration Platform for Mobile Computing. *Cooperative Design, Visualization, and Engineering*, 123-131.

- Quinn, L., Mehta, P., and Sicher, A. (2005). *Wireless communications technology landscape*. Technical report.
- Rajinder, S. N. (2004). *Cartographic visualisation for mobile application*. Master's thesis, ITC/IIRS.
- Ramsak, F. et al (2000). *Integrating the UB-tree into a Database System Kernel*. *Int. Conf. on Very Large Databases, (VLDB)*, pp 263-272.
- Reza, A. W., Eswaran, C., Hati, S. (2007). Diabetic Retinopathy: A Quadtree Based Blood Vessel Detection Algorithm Using RGB Components in Fundus Images. *Journal of Medical Systems*, 147-155.
- Rivest, S., Bédard, S., Marchand, P. (2001). *Toward better support for spatial decision making: Defining the characteristics of spatial on-line analytical processing (SOLAP)*, " *Geomatica*, Vol. 55(4), 539–555.
- Sahr, K., White, D., Kimerling, A. J. (2003). Geodesic Discrete Global Grid Systems. *Cartography and Geographic Information Science*, 30(2), 121-134.
- Samet, R. & Ozsavas, E. (2007). Optimization of Quadtree Triangulation for Terrain Models. *Advanced Concepts for Intelligent Vision Systems*, 48-59.
- Sarjakoski, L. T., Koivula, T., Sarjakoski, T. (2007). A Knowledge-Based Map Adaptation Approach for Mobile Map Services. *Location Based Services and TeleCartography*, 247-264.
- Sasaoka, L. K., & Medeiros, C. B. (2006). Access Control in Geographic Databases. *Advances in Conceptual Modeling - Theory and Practice*, 110-119.
- Satyanarayanan, M. (1995). Fundamental Challenges in Mobile Computing. *Symposium on Principles of Distributed Computing*.
- Shekhar, S. (1999). Spatial Databases – Accomplishments and Research Needs. *IEEE Tran. Knowledge and Data Engineering*, Vol. 11, No. 1, 45-55.
- Spinney, J. E. (2003). *Mobile positioning and LBS applications*. *Geography*, 88(4), 256-265.
- Steinbruch, F., & Macario, L. (2006). Linking databases of different sources and scales for groundwater research in the Urema River Basin/Central Mozambique. *Water Resources Management*, 171-184.
- Takino, S. (2001). "GIS on the fly" To realize wireless GIS network by java mobile phone. International Symposium on Asia GIS 2001.

- Tang, W. and Selwood, J. (2003). *Mobile geographic information service (m-gis) technology that changes the way we navigate our world*. Geospatial Engineering, 5(2):43–50.
- Tanin, E., Harwood, A., Samet, H. (2006). Using a distributed quadtree index in peer-to-peer networks. *The VLDB Journal The International Journal on Very Large Data Bases*, 165-178.
- Tham, C. (1993). *Performance Tuning for Relational Database Applications*.
- Timpf, S. (2006). Way finding with mobile devices: decision support for the mobile citizen. *Frontiers of Geographic Information Technology*, 209-228.
- Tropf, H., & Herzog, H. (1981). *Multidimensional Range Search in Dynamically Balanced Trees*, Angewandte Informatik, pp 71-77.
- Tzouramanis, T., Vassilakopoulos, M., Manolopoulos, Y. (2000). Multiversion Linear Quadtree for Spatio-Temporal Data. *Current Issues in Databases and Information Systems*, 279-292.
- Uzel, A. R. (1987). *Guidelines for Expert System Applications*. CEM, February 1987, pp. 40-45.
- Valensise, G., & Pantosti, D. (2001). Database of potential sources for earthquakes larger than 5.5 in Italy. *Ann Geofis, supplement to vol. 44 (4)*, 180.
- Vckovski, A. (1999). Interoperability and spacial information theory. *Interoperating Geographic Information Systems*.
- Vilardo, G., Nappi, R., Petti, P., Ventura, G. (2003). *Fault geometries from the space distribution of the 1990-1997 Sannio-Benevento earthquakes: inferences on the active deformation in Southern Apennines*. Tectonophysics, 363(3–4), 259-271.
- Vilardo, G., Terranova, C., Bronzino, G., Giordano, S., Ventura, G., Alessio, G., Gabriele, M., Mainolfi, R., Pagliuca, E., Veneruso, M. (2001). *SISCam: Sistema Informativo Sismotettonico della Regione Campania*. http://ipf.ov.ingv.it/lgc/progetti_gb.asp.
- Yeung, A., & Hall, G. (2007). Trends of Spatial Database Systems. *Spatial Database Systems*, 471-522.
- Yeung, A. & Hall, G. (2007). Spatial Data Sharing, Data Warehousing and Database Federation. *Spatial Database Systems*, 175-216.
- Yodor, P. R. (1997). *Opto-mechanical System Design*. Marcel Dekker.

- You, B. S., Kim, G. B., Bae, H. Y. (2007). Cluster Recovery for Fault Tolerance of Spatial Database Cluster in Sensor Networks. *Parallel and Distributed Processing and Applications*, 395-406.
- Yun J. K., Kim J. J., Hong D. K. and Han K. J. (2005). Development of an Embedded Spatial MMDBMS for Spatial Mobile Devices. *Web and Wireless Geographical Information Systems*, 1-10.
- Yun, J. K., Kim, D. O., Hong, D. S., Kim, M. H., Han, K.J. (2006). A real-time mobile GIS based on the HBR-treenext term for location based services. *Computers & Industrial Engineering*, Volume 51, Issue 1, September 2006, pp 58-71.
- Zhang, L. & Xi, L. F. (2007). A Novel Fractal Image Coding Based on Quadtree Partition of the Adaptive Threshold Value. *Theoretical Advances and Applications of Fuzzy Logic and Soft Computing*, 504-512.
- Zhu, Q., Gong, J., Zhang, J. (2007). An efficient 3D R-tree spatial index method for virtual geographic environments. *ISPRS Journal of Photogrammetry and Remote Sensing*, Volume 62, Issue 3, August 2007, pp 217-224.
- Zimbrao, G., & Souza, J. M. (1998). A Raster Approximation for Processing of Spatial Joins. In: *Proceedings of the 24th International Conference on Very Large Data Bases*, New York City, New York, USA, 558-569.